



SECTION 1 PRODUCT NAME AND COMPANY IDENTIFICATION

Product Name: KM 1213 - Acrylic Premium Elastomeric Sealant with StretchSpan Technology™

Recommended Use: Roofing and other construction applications.

Restriction on Use: None

Manufacturer: KM Coatings Mfg. 5301 W. Mohave Street Phoenix, AZ 85043 (602)-253-1168

SDS Date of Preparation: 11/3/17

Emergency Contact: (800) 424-9300 CHEMTREC (USA)

SECTION 2: HAZARDS IDENTIFICATION

Hazard Classification:

Physical	Health
Not Hazardous	Carcinogen Category 2

Label Elements:



WARNING! Suspected of causing cancer by ingestion.

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, clothing and eye protection **Response** If exposed or concerned: Get medical advice. **Storage** Store locked up. **Disposal:** Dispose of contents and container in accordance with local and national regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS



SAFETY DATA SHEET

INGREDIENTS	CAS#.	<u>WT.%</u>
Acrylic Polymer	Proprietary	20-40
Calcium Carbonate	1317-65-3	20-30
Titanium Dioxide	13463-67-7	5-10
	10400-01-1	5-10
Zinc Oxide	1314-13-2	1-5
Crystalline Silica, Quartz	14808-60-7	0.1-1
Benzophenone	119-61-9	0.1-0.5

Note: The crystalline silica and titanium dioxide in this product are inextricably bound so no exposure will occur and the carcinogen classification does not apply to these chemicals.

The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURERS

Eyes: Immediately flush eyes with water while lifting the upper and lower lids. Get medical attention if irritation persists.

Skin: Remove contaminated clothing. Wash skin thoroughly with soap and water. If irritation develops, get medical attention. Launder clothing before re-use.

Inhalation: If symptoms develop, remove victim to fresh air. If symptoms develop, get medical attention.

Ingestion: If conscious, rinse mouth with water. Never give anything by mouth to a person who is unconscious or convulsing. If large amount if swallowed or gastrointestinal effects develop, get medical attention.

Most important symptoms/effects, acute and delayed: Causes mild eye irritation. Prolonged contact may cause skin irritation and dryness. Inhalation of vapors may cause respiratory irritation. Ingestion may cause nausea, vomiting and diarrhea.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention is not normally required.

SECTION 5 FIRE FIGHTING MEASURES





Extinguishing Media: Use any media appropriate for the surrounding fire. Cool fire exposed containers with water

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Do not allow run-off from firefighting to enter drains or water courses

Specific Hazards Arising from the Chemical: This product is an aqueous mixture that will not burn until all water has evaporated. Residue will burn after the fire has evaporated. Combustion products may include oxides of carbon and zinc.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Wear appropriate protective clothing to avoid eye and skin contact. Collect spilled material with inert material and place into a closable container for disposal. Prevent runoff to storm sewers and ditches leading to natural waterways.

Environmental precautions: Avoid release to the environment. Report releases as required by local, state and federal authorities.

Methods and Materials for Containment and Cleaning Up: Wipe up and place into a closable container for disposal.

SECTION 7 HANDLING and STORAGE

Precautions for Safe Handling: Avoid contact with the eyes, skin and clothing. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use.

Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a dry, well-ventilated area. Protect from physical damage. Store in original container; keep tightly closed. Rotate stock, using older materials first. Do not reuse container for other purposes. Do not store in freezing areas. Keep above 40 °F, but less than 100 °F. Do not store in direct sunlight.

SECTION 8 EXPOSURE CONTROLS and PERSONAL PROTECTION

Exposure Guidelines:

INGREDIENTS	EXPOSURE LIMITS	
Acrylic Polymer	None Established	
Calcium Carbonate	5 mg/m3 TWA OSHA PEL (respirable fraction)	
	15 mg/m3 TWA OSHA PEL (total dust)	
Titanium Dioxide	15 mg/m3 TWA OSHA PEL (total dust)	
	10 mg/m3 TWA ACGIH TLV	
Zinc Oxide	5 mg/m3 TWA OSHA PEL (respirable fraction)	
	15 mg/m3 TWA OSHA PEL (total dust)	
	2 mg/m3 TWA ACGIH TLV, 10 mg/m3 STEL (respirable) ACGIH TLV	
Crystalline Silica, Quartz	0.05 mg/m3 TWA OSHA PEL (respirable dust)	
· · · · · · · · · · · · · · · · · · ·	0.025 mg/m3 TWA ACGIH TLV (respirable fraction)	
Benzophenone	0.5 mg/m ³ TWA AIHA WEEL	





Appropriate Engineering Controls: Use with adequate ventilation to maintain exposures below the occupational exposure limits.

Respiratory Protection: If the exposure limits are exceeded a NIOSH approved respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Gloves: Rubber or other impervious gloves are recommended to prevent prolonged skin contact.

Eye Protection: Chemical safety goggles should be worn if splashing is possible.

Other Protective Equipment: Impervious clothing as needed to avoid contact.

SECTION 9 PHYSICAL and CHEMICAL PROPERTIES

Appearance And Odor: White paste, slight ammonia odor..

Boiling Point (@ 760 mmHg): Not determined	Freezing Point: not available	
Odor Threshold: Not determined	Viscosity: Not determined	
Relative density (H2O=1): 1.34	Vapor Pressure: Not determined	
VOC: <50 g/L	Vapor Density (AIR=1): Not determined	
Evaporation Rate: Not available	Solubility In Water: Soluble	
pH: 8.35	Partition Coefficient n-Octanol/Water: Not determined	
lash Point: >212°F (>100°C) Setaflash Autoignition Temperature: Not available		
ecomposition Temperature: Not available Flammability (solid, gas): Not applicable		
Flammable Limits: (vol % in air) LEL – Not applicable UEL – Not applicable		

SECTION 10 STABILITY and REACTIVITY

Reactivity: Not normally reactive.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known.

Conditions to avoid: None known.

Incompatible materials: Avoid oxidizing agents and acids.

Hazardous decomposition products: Thermal decomposition may yield oxides of carbon and zinc.

SECTION 11 TOXICOLOGICAL INFORMATION

Eye: Contact may cause irritation with redness and tearing.

Skin: Prolonged skin contact may cause irritation and drying of the skin.

Inhalation: Inhalation of vapors may cause mucous membrane and respiratory irritation

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sensitization: This product is not expected to cause sensitization.

Chronic Effects: Repeated inhalation of large amounts of silica dust over an extended period of time may result in a progressive, disabling disease, silicosis. However, the crystalline silica in this product is bound in the liquid polymer matrix and dust exposure would not be expected.

Carcinogenicity: Titanium dioxide is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B. Respirable crystalline silica is classified as a Group 1 carcinogen by IARC, and "Known to be a Human Carcinogen" by NTP. However, the crystalline silica and titanium dioxide in this product are bound in the polymer matrix and dust exposure would not be expected. Benzophenone is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B. None of the other components present at 0.1% or greater are listed as a carcinogen by NTP. IARC or OSHA.

Numerical Measures of Toxicity:



SAFETY DATA SHEET

Acrylic Polymer: Oral rat LD50 >5000 mg/kg, Dermal rabbit LD50 >5000 mg/kg Calcium Carbonate: No toxicity data available Titanium Dioxide: No toxicity data available Zinc Oxide: Oral rat LC50>5 g/kg, Inhalation mouse LC50 >5.7 mg/L/4 hr Crystalline Silica: Oral rat LD50: >10,000 mg/kg; Inhalation rat LC50: >0.139 mg/l/4 hr; Skin rabbit LD50: >5000 mg/kg Benzophenone: Oral mouse LD50 2895 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Zinc oxide is classified as very toxic to aquatic organisms. LC50 zebra fish 1.8 mg/L/96 hr; IC50 algae 0.136 mg/L Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available Other adverse effects: No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with all local, state and federal regulations.

SECTION 14: TRANSPORT INFORMATION

DOT:

2011	UN/ID Number Proper Shipping Name Hazard Class Packing Group ERG Code DOT Special Provisions Description	None Not Regulated None N/A None known None
TDG:		
	UN/ID Number Proper Shipping Name Hazard Class Packing Group ERG Code TDG Special Provisions Description	None Not Regulated None N/A None known None
IATA:		
	UN/ID Number Proper Shipping Name Hazard Class Packing Group ERG Code Special Provisions Description	None Not Regulated None N/A None known None
IMDG:	UN/ID Number Proper Shipping Name Hazard Class	None Not Regulated None



SAFETY DATA SHEET

None
N/A
None known
None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None known

SECTION 15: REGULATORY INFORMATION

SARA Hazard Category (311/312): r to Section 2 for OSHA Hazard Classification.

EPA SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313: None Zinc Oxide (as Zinc Compounds) 1-5 %

CERCLA Hazardous Substances (Section 103)/RQ: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory.

California Proposition 65: This product contains chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: OTHER INFORMATION			
NFPA Rating:	Health = 1	Fire = 0	Instability = 0
HMIS Rating:	Health = 1*	Fire = 0	Physical Hazard = 0

SDS Date of Preparation: 11/3/17

Revision Summary: Header, Section 8 Exposure Limit, Section 14 Transportation, Section 15 SARA 311/312

NOTICE

The information contained herein is based upon the data available to us and is believed to be accurate. However, KM Coatings Mfg. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. KM Coatings Mfg. assumes no responsibility for injury from the use of the products described herein.

This SDS conforms with the OSHA Hazard Communication Standard 1900.1210 and to SARA Title III, Section 313 for supplier notification.