# Safety Data Sheet KM ACRYL 40

Safety Data Sheet dated: 08/21/2023 - version 1

Date of first edition: 08/21/2023



#### 1. IDENTIFICATION

#### **Product identifier**

Mixture identification:

Trade name: KM ACRYL 40 Trade code: 905acr40g

Recommended use of the chemical and restrictions on use

Recommended use: Acrylic paint Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: KM Coatings Mfg.

5301 W. Mohave Street 85043 - Phoenix - AZ - USA Phone: 602-253-1168

Responsible: Not available **Emergency 24 hour numbers:** Chemtrec (800) 424-9300

# 2. HAZARD(S) IDENTIFICATION





# Classification of the chemical

Acute aquatic hazard, category 2

Chronic (long term) aquatic hazard, category 2

Carcinogenicity, Category 1A

Toxic to aquatic life

Toxic to aquatic life with long lasting effects.

May cause cancer if swallowed.

# Label elements

# Hazard pictograms and Signal Word



Danger

#### **Hazard statements**

H350 May cause cancer if swallowed.

H401 Toxic to aquatic life

H411 Toxic to aquatic life with long lasting effects.

# **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P391 Collect spillage.
P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

# Ingredient(s) with unknown acute toxicity:

None

# Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized

Print date 08/21/2023 Production Name KM ACRYL 40 Page n. 1 of 9

crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substances

Not Relevant

#### **Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

#### List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
5-10 %	titanium dioxide; Dioxotitanium	CAS:13463-67-7 EC:236-675-5 Index:022-006- 00-2	Carc. 2, H351	
1-2.5 %	zinc oxide; oxozinc	CAS:1314-13-2 EC:215-222-5 Index:030-013- 00-7	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
0.1-0.25 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350	
0.1-0.25 %	benzophenone; di(phenyl)methanone	CAS:119-61-9 EC:204-337-6	STOT RE 2, H373; Aquatic Acute 2, H401; Aquatic Chronic 3, H412; Carc. 1B, H350	

#### 4. FIRST AID MEASURES

#### Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

# Most important symptoms/effects, acute and delayed

Not available

#### Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

# 5. FIRE-FIGHTING MEASURES

# **Extinguishing media**

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

# Unsuitable extinguishing media:

None in particular.

#### Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant

Print date 08/21/2023 Production Name KM ACRYL 40 Page n. 2 of 9

Oxidizing properties: Not available

#### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### **6. ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

#### Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

#### Conditions for safe storage, including any incompatibilities

Store above freezing

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

Community Occupational Exposure Limits (OEL)					
	OEL Type	Country	Occupational Exposure Limit		
titanium dioxide; Dioxotitanium CAS: 13463-67-7	OSHA		Long Term: 15 mg/m3		
	ACGIH		Long Term: 10 mg/m3 A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation;		
	MAK	GERMANY	Long Term: 0.3 mg/m3		
	ACGIH		Long Term: 10 mg/m3 A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation		
	MAK	AUSTRIA	Long Term: 5 mg/m3; Short Term: 10 mg/m3		
	MAK	SWITZERLAN D	Long Term: 3 mg/m3		
zinc oxide; oxozinc CAS: 1314-13-2	OSHA		Long Term: 5 mg/m3		
	OSHA		Long Term: 15 mg/m3		
	ACGIH		Long Term: 2 mg/m3; Short Term: 10 mg/m3 metal fume fever;		
	ACGIH		Long Term: 2 mg/m3; Short Term: 10 mg/m3 metal fume fever		

Print date 08/21/2023 Production Name KM ACRYL 40 3 of 9 Page n.

MAK AUSTRIA Long Term: 5 mg/m3 MAK SWITZERLAN Long Term: 3 mg/m3

D

silica sand; quartz CAS: 14808-60-7 ACGIH Long Term: 0.025 mg/m3

A2 - Suspected Human Carcinogen; lung cancer; pulmonary fibrosis;

ACGIH Long Term: 0.025 mg/m3

A2 - Suspected Human Carcinogen; lung cancer; pulmonary fibrosis

MAK AUSTRIA Long Term: 0.15 mg/m3 MAK SWITZERLAN Long Term: 0.15 mg/m3

D

Appropriate engineering controls: Not available

#### Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min. Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid white/grey

Odour: mild

Odour threshold: Not Relevant

pH: 9.20

Melting point / freezing point: Not Relevant
Initial boiling point and boiling range: Not Relevant

Flash point: 100 °C (212 °F) Evaporation rate: Not Relevant

Upper/lower flammability or explosive limits: Not Relevant

Vapour density: Not Relevant
Vapour pressure: Not Relevant
Relative density: 1.31 g/cm3
Solubility in water: easily soluble
Solubility in oil: Not Relevant

Partition coefficient (n-octanol/water): Not Relevant

Auto-ignition temperature: Not Relevant Decomposition temperature: Not Relevant

Viscosity: Not Relevant

Explosive properties: Not Relevant Oxidizing properties: No data available Solid/gas flammability: Not Relevant

# Other information

Substance Groups relevant properties Not Relevant

Miscibility: Not Relevant Fat Solubility: Not Relevant Conductivity: Not Relevant

# 10. STABILITY AND REACTIVITY

Print date 08/21/2023 Production Name KM ACRYL 40 Page n. 4 of 9

# Reactivity

Stable under normal conditions

#### Chemical stability

Data not available.

#### Possibility of hazardous reactions

None.

#### **Conditions to avoid**

Stable under normal conditions.

#### **Incompatible materials**

None in particular.

#### **Hazardous decomposition products**

None.

#### 11. TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

# **Toxicological Information of the Preparation**

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity The product is classified: Carcinogenicity, Category 1A(H350)

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

# Toxicological information on main components of the mixture:

titanium dioxide; Dioxotitanium a) acute toxicity

LD50 Oral Rat > 10000 mg/kg

zinc oxide; oxozinc

a) acute toxicity

., acate to ......

LD50 Oral Rat > 5000 mg/kg LD50 Oral Rat > 5000 mg/kg

silica sand; quartz

di(phenyl)methanone

a) acute toxicity

LD50 Oral Rat = 500 mg/kg

benzophenone;

a) acute toxicity

LD50 Skin Rabbit = 3535 mg/kg

LD50 Oral Rat > 10 g/kg

LD50 Skin Rabbit = 3535 mg/kg

LD50 Oral Rat > 10 g/kg

#### Substance(s) listed on the IARC Monographs:

titanium dioxide; Dioxotitanium Group 2B silica sand; quartz Group 1 benzophenone; Group 2B

Print date 08/21/2023 Production Name KM ACRYL 40 Page n. 5 of 9

#### Substance(s) listed as OSHA Carcinogen(s):

titanium dioxide; Dioxotitanium

silica sand; quartz

benzophenone; di(phenyl)methanone

#### Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide; Dioxotitanium

silica sand; quartz

#### Substance(s) listed on the NTP report on Carcinogens:

silica sand: quartz

#### 12. ECOLOGICAL INFORMATION

#### **Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

#### List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 2(H401), Chronic (long term) aquatic hazard, category 2(H411)

#### List of Eco-Toxicological properties of the components

Component Ident. Numb. Ecotox Data

zinc oxide; oxozinc CAS: 1314-13-2 a) Aquatic acute toxicity: LC50 Fish Danio rerio = 1.55 mg/L 96h ECHA

- EINECS: 215-222-5 - INDEX: 030-013-00-7

silica sand; quartz CAS: 14808-60- a) Aquatic acute toxicity: LC50 carp > 10000 mg/L 72h

7 - EINECS: 238-878-4

benzophenone; CAS: 119-61-9 - a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 13.2 mg/L 96h EPA

di(phenyl)methanone EINECS: 204-

337-6

# Persistence and degradability

N.A.

# **Bioaccumulative potential**

N.A.

# Mobility in soil

N.A.

# Other adverse effects

N.A.

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

# Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

Print date 08/21/2023 Production Name KM ACRYL 40 Page n. 6 of 9

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

#### 14. TRANSPORT INFORMATION

#### **UN** number

DOT-UN Number: Not Applicable

ADR-UN number: 3082 IATA-Un number: 3082 IMDG-Un number: 3082

# **UN** proper shipping name

DOT-Proper Shipping Name: (Not regulated for US DOT) (zinc oxide)

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide) IATA-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide) IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide)

# Transport hazard class(es)

DOT-Hazard Class: Not Applicable

ADR-Class: 9
IATA-Class: 9
IMDG-Class: 9

#### Packing group

DOT Packing Group: Not Applicable

ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

#### **Environmental hazards**

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: No

#### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

# **Special precautions**

Department of Transportation (DOT):

Road and Rail ( ADR-RID ) :

ADR-Label: 9

ADR-Hazard identification number: 90

ADR-Transport category (Tunnel restriction code): 3 (-)

Air ( IATA ):

IATA-Passenger Aircraft: 964 IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisioning: A97 A158 A197 A215

Sea ( IMDG ):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 274 335 969

IMDG-EMS: F-A, S-F

# 15. REGULATORY INFORMATION

#### **USA** - Federal regulations

# **TSCA - Toxic Substances Control Act**

All the components are listed on the TSCA inventory

**TSCA listed substances:** 

titanium dioxide; Dioxotitanium is listed in TSCA Section 8b

Print date 08/21/2023 Production Name KM ACRYL 40 Page n. 7 of 9

zinc oxide; oxozinc is listed in TSCA Section 8b silica sand; quartz is listed in TSCA Section 8b

benzophenone; is listed in TSCA Section 8b Section 12b

di(phenyl)methanone

#### SARA - Superfund Amendments and Reauthorization Act

#### Section 302 - Extremely Hazardous Substances:

No substances listed

#### Section 304 - Hazardous substances:

No substances listed

#### Section 313 - Toxic chemical list:

zinc oxide; oxozinc

# CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

No substances listed

#### CAA - Clean Air Act

#### **CAA listed substances:**

benzophenone; is listed in CAA Section 112(b) - HON

di(phenyl)methanone

#### **CWA - Clean Water Act**

#### **CWA listed substances:**

No substances listed

#### **USA - State specific regulations**

#### **California Proposition 65**

#### Substance(s) listed under California Proposition 65:

titanium dioxide; Dioxotitanium Listed as carcinogen silica sand; quartz Listed as carcinogen benzophenone; Listed as carcinogen

di(phenyl)methanone

#### Massachusetts Right to know

#### Substance(s) listed under Massachusetts Right to know:

titanium dioxide; Dioxotitanium

zinc oxide; oxozinc silica sand; quartz

# Pennsylvania Right to know

# Substance(s) listed under Pennsylvania Right to know:

titanium dioxide; Dioxotitanium

zinc oxide; oxozinc silica sand; quartz

# New Jersey Right to know

# Substance(s) listed under New Jersey Right to know:

titanium dioxide; Dioxotitanium

zinc oxide; oxozinc silica sand; quartz

#### **Canada - Federal regulations**

#### **DSL - Domestic Substances List**

All the substances are listed in the DSL.

# **NDSL - Non Domestic Substances List**

This product complies with NDSL inventory

# **NPRI - National Pollutant Release Inventory**

# NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

Print date 08/21/2023 Production Name KM ACRYL 40 Page n. 8 of 9

#### **16. OTHER INFORMATION**

Safety Data Sheet dated: 8/21/2023 - version 1

#### Additional classification information

NFPA Health: 0 = Minimal

NFPA Flammability: 1 = Combustible if heated

NFPA Reactivity: 0 = Minimal NFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description			
H350	May cause cancer.			
H351	Suspected of causing cancer.			
H372	Causes damage to organs through prolonged or repeated exposure.			
H373	May cause damage to organs through prolonged or repeated exposure.			
H400	Very toxic to aquatic life.			
H401	Toxic to aquatic life			
H410	Very toxic to aquatic life with long lasting effects.			
H412	Harmful to aquatic life with long lasting effects.			
Code	Hazard class and hazard category	Description		
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A		
A.6/1B	Carc. 1B	Carcinogenicity, Category 1B		
A.6/2	Carc. 2	Carcinogenicity, Category 2		
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1		
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2		
US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1		
US-HAE/A2	Aquatic Acute 2	Acute aquatic hazard, category 2		
US-HAE/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1		
US-HAE/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3		

# Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Print date 08/21/2023 Production Name KM ACRYL 40 Page n. 9 of 9