

SECTION 1 PRODUCT NAME AND COMPANY IDENTIFICATION

Product Name: KM Acryl 25-QS

Recommended Use: Roof Coating

Restriction on Use: None

Manufacturer: KM Coatings Mfg. 1719 W. Buchanan Street Phoenix, AZ 85007 (602)-253-1168

SDS Date of Preparation: 11/3/17

Emergency Contact: (800) 424-9300 CHEMTREC (USA)

SECTION 2: HAZARDS IDENTIFICATION

Hazard Classification:

Physical	Health
Not Hazardous	Carcinogen Category 2

Label Elements:

None Required

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS#.	<u>WT.%</u>
Calcium Carbonate	1317-65-3	30-50
Titanium Dioxide	13463-67-7	5-10
Zinc Oxide	1314-13-2	1-5
Crystalline Silica, Quartz	14808-60-7	0.1-1
Benzophenone	119-61-9	0.1-0.5

Note: The crystalline silica and titanium dioxide in this product are inextricably bound so no exposure will occur and the carcinogen classification does not apply for these chemicals.

The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURERS

Eyes: Flush eyes with water while lifting the upper and lower lids. Get medical attention if irritation persists.

Skin: Remove contaminated clothing. Wash skin thoroughly with soap and water. If irritation develops, get medical attention. Launder clothing before re-use.



Inhalation: If symptoms develop, move to fresh air. If symptoms persist, get medical attention.

Ingestion: If conscious, rinse mouth with water. Never give anything by mouth to a person who is unconscious or convulsing. If large amount if swallowed or gastrointestinal effects develop, get medical attention.

Most important symptoms/effects, acute and delayed: Causes mild eye irritation. Prolonged contact may cause skin irritation and dryness. Inhalation of vapors or mists may cause respiratory irritation. Ingestion may cause nausea, vomiting and diarrhea.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention is not normally required.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media: Use any media appropriate for the surrounding fire. Cool fire exposed containers with water. Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Do not allow run-off from firefighting to enter drains or water courses. Specific Hazards Arising from the Chemical: This product is an aqueous mixture that will not burn until all water has evaporated. Residue will burn after the fire has evaporated. Combustion products may include oxides of carbon and zinc.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Wear appropriate protective clothing to avoid eye and skin contact.

Methods and Materials for Containment and Cleaning Up: Dike the spilled material. Attempt to reclaim the free product, if this is possible. Place in an appropriate container for use or disposal. Collect residue with inert material and place into a closable container for disposal. Wash spill area. Prevent runoff to storm sewers and ditches leading to natural waterways. Report spill as required by local and federal regulations.

SECTION 7 HANDLING and STORAGE

Precautions for Safe Handling: Avoid contact with the eyes. Avoid prolonged contact with skin and clothing. Avoid breathing vapors and mists. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use.

Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a dry, well-ventilated area. Protect from physical damage. Store in original container; keep tightly closed. Rotate stock, using older materials first. Do not reuse container for other purposes. Do not store in freezing areas. Keep above 40 °F, but less than 100 °F. Do not store in direct sunlight.



SECTION 8 EXPOSURE CONTROLS and PERSONAL PROTECTION

Exposure Guidelines:

INGREDIENTS	EXPOSURE LIMITS	
Calcium Carbonate	5 mg/m ³ TWA OSHA PEL (respirable fraction)	
	15 mg/m ³ TWA OSHA PEL (total dust)	
Titanium Dioxide	15 mg/m ³ TWA OSHA PEL (total dust)	
	10 mg/m ³ TWA ACGIH TLV	
Zinc Oxide	5 mg/m ³ TWA OSHA PEL (respirable fraction)	
	15 mg/m ³ TWA OSHA PEL (total dust)	
	2 mg/m ³ TWA ACGIH TLV, 10 mg/m3 STEL (respirable)	
Crystalline Silica, Quartz	0.05 mg/m3 TWA OSHA PEL (respirable dust)	
	0.025 mg/m ³ TWA ACGIH TLV (respirable fraction)	
Benzophenone	0.5 mg/m3 TWA AIHA WEEL	

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits.

Respiratory Protection: If the exposure limits are exceeded a NIOSH approved respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Gloves: Rubber or other impervious gloves are recommended to prevent prolonged skin contact.

Eye Protection: Chemical safety goggles should be worn if splashing is possible.

Other Protective Equipment: Impervious clothing as needed to avoid skin contact.

SECTION 9 PHYSICAL and CHEMICAL PROPERTIES

Appearance And Odor: White paste-Bland Odor.

Boiling Point (@ 760 mmHg): Not determined	Freezing Point: Not available
Odor Threshold: Not determined	Viscosity: Not determined
Relative density (H2O=1): Not determined	Vapor Pressure: Not determined
VOC: Not determined	Vapor Density (AIR=1): Not determined
Evaporation Rate: <1 (BuOAc=1)	Solubility In Water: Soluble
pH: Not available	Partition Coefficient n-Octanol/Water: Not available
Flash Point: >200°F (>93.3°C)	Autoignition Temperature: Not applicable
Decomposition Temperature: Not determined	Flammability (solid, gas): Not applicable
Flammable Limits: (vol % in air) LEL – Not applicable UEL – Not applicable	

SECTION 10 STABILITY and REACTIVITY

Reactivity: Not normally reactive.

Chemical Stability: Stable under normal storage and handling conditions

Possibility of Hazardous Reactions: None known

Conditions to avoid: None known.

Incompatible materials: Avoid oxidizing agents and acids

Hazardous decomposition products: Thermal decomposition may yield oxides of carbon and zinc.



SECTION 11 TOXICOLOGICAL INFORMATION

Eye: Contact may cause irritation with redness and tearing

Skin: Prolonged skin contact may cause irritation and drying of the skin.

Inhalation: Inhalation of vapors or mists may cause mucous membrane and upper respiratory tract irritation **Ingestion:** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. **Sensitization:** This product is not expected to cause sensitization.

Chronic Effects: This product contains a very small amount of naturally occurring crystalline silica. Repeated inhalation of large amounts of silica dust over an extended period of time may result in a progressive, disabling disease, silicosis. However, the crystalline silica in this product is in polymer matrix and dust exposure would not be expected.

Carcinogenicity: Titanium dioxide is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B. Respirable crystalline silica is classified as a Group 1 carcinogen by IARC, and "Known to be a Human Carcinogen" by NTP. However, the crystalline silica and titanium dioxide in this product are bound in the polymer matrix and dust exposure would not be expected. Benzophenone is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B. None of the other components present at 0.1% or greater are listed as a carcinogen by NTP, IARC, ACGIH or OSHA.

Numerical Measures of Toxicity:

Calcium Carbonate: Oral rat LD50: 6450 mg/kg Titanium Dioxide: Oral rat LD50: >5000 mg/kg Zinc Oxide: Oral rat LD 50 >5 g/kg, Inhalation mouse LC50 >5.7 mg/L/4 hr. Crystalline Silica: Oral rat LD50: >10,000 mg/kg; Inhalation rat LC50: >0.139 mg/l/4 hr; Skin rabbit LD50: >5000 mg/kg Benzophenone: Oral mouse LD50 2895 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Zinc oxide is classified as very toxic to aquatic organisms. LC50 zebra fish 1.8 mg/L/96 hr; IC50 algae 0.136 mg/L Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available Other adverse effects: No data available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with all local, state and federal regulations.

SECTION 14: TRANSPORT INFORMATION

DOT:		
	UN/ID Number	None
	Proper Shipping Name	Not Regulated
	Hazard Class	None
	Packing Group	None
	ERG Code	N/A
	DOT Special Provisions	None known
	Description	None
TDG:		
	UN/ID Number	None
	Proper Shipping Name Hazard Class	Not Regulated None

SAFETY DATA SHEET



	Packing Group ERG Code TDG Special Provisions Description	None N/A None known None
IATA*:		
	UN/ID Number Proper Shipping Name* Hazard Class Packing Group ERG Code Special Provisions Description	UN3082 Environmentally Hazardous Substance, liquid n.o.s (zinc oxide) 9 III 171 A97, A158, A197 UN3082, Environmentally Hazardous Substance, liquid n.o.s (zinc oxide), 9, III
IMDG*:		
	UN/ID Number Proper Shipping Name Hazard Class Packing Group EmS-No Special Provisions Description	UN3082 Environmentally Hazardous Substance, liquid n.o.s (zinc oxide) 9 III F-A, S-F 274, 335, 969 UN3082, Environmentally Hazardous Substance, liquid n.o.s (zinc oxide), 9, III, Marine Pollutant

* This product is classified as a Marine Pollutant (Environmentally Hazardous Substance) in accordance with the IMDG Code and the UN Model Regulations. However, if it is packaged in either single packages or inner packagings in combination packages containing net quantities of less than 5 kg/5 L, the Marine Pollutant does not apply (IMDG Code 2.10.2.7).

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None known

SECTION 15: REGULATORY INFORMATION

SARA Hazard Category (311/312): Refer to Section 2 for OSHA Hazard Classification.

EPA SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313: Zinc Oxide (as Zinc Compounds) 1- 5 %

CERCLA Hazardous Substances (Section 103)/RQ: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory.

California Proposition 65: This product contains chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: OTHER INFORMATION

NFPA Rating: HMIS Rating: Health = 1 Health = 1^* Fire = 0Fire = 0 Instability = 0 Physical Hazard = 0



SAFETY DATA SHEET

SDS Date of Preparation: 11/3/17

Revision Summary: Header, Section 8 Exposure Limit, Section 14 Transportation, Section 15 SARA 311/312

NOTICE

The information contained herein is based upon the data available to us and is believed to be accurate. However, KM Coatings Mfg. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. KM Coatings Mfg. assumes no responsibility for injury from the use of the products described herein.

This MSDS conforms to the OSHA Hazard Communication Standard 1900.1210 and to SARA Title III, Section 313 for supplier notification.