

SECTION 1 PRODUCT NAME AND COMPANY IDENTIFICATION

Product Name: Primeseal 1

Recommended Use: Roofing and other construction applications

Restriction on Use: None

Manufacturer: KM Coatings Mfg. 1719 W. Buchanan Street Phoenix, AZ 85007 (602)-253-1168

SDS Date of Preparation: 11/3/17

Emergency Contact: (800) 424-9300 CHEMTREC (USA)

SECTION 2: HAZARDS IDENTIFICATION

Hazard Classification:

Physical	Health
Not Hazardous	Not Hazardous

Label Elements:

Not Hazardous in accordance with the Globally Harmonized System for the Classification and Labeling of Chemicals (GHS)

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

 INGREDIENTS
 CAS#.
 WT.%

 Carbon Black
 1333-86-4
 <1</td>

Note: The carbon black in this product is inextricably bound so no exposure will occur and the carcinogen classification does not apply

The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURERS

Eyes: Flush eyes with water while lifting the upper and lower lids. Get medical attention if irritation persists.

Skin: Remove contaminated clothing. Wash skin thoroughly with soap and water. If irritation develops, get medical attention. Launder clothing before re-use.

Inhalation: If symptoms develop, move to fresh air. If symptoms persist, get medical attention.

Ingestion: If conscious, rinse mouth with water. Never give anything by mouth to a person who is unconscious or convulsing. If large amount if swallowed or gastrointestinal effects develop, get medical attention.

Primeseal 1 Page 1 of 5



Most important symptoms/effects, acute and delayed: May cause mild eye irritation. Prolonged contact may cause mild skin irritation and dryness.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention is not normally required.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media: Use any media appropriate for the surrounding fire. Cool fire exposed containers with water. **Special Protective Equipment and Precautions for Fire-fighters:** Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Do not allow run-off from firefighting to enter drains or water courses. **Specific Hazards Arising from the Chemical:** This product is an aqueous mixture that will not burn until all water has evaporated. Residue will burn after the fire has evaporated. Combustion products may include oxides of carbon.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Wear appropriate protective clothing to avoid eye and skin contact.

Environmental precautions: Avoid release to the environment. Report releases as required by local, state and federal authorities.

Methods and Materials for Containment and Cleaning Up: Dike the spilled material. Attempt to reclaim the free product, if this is possible. Place in an appropriate container for use or disposal. Collect residue with inert material and place into a closable container for disposal. Wash spill area. Prevent runoff to storm sewers and ditches leading to natural waterways. Report spill as required by local and federal regulations.

SECTION 7 HANDLING and STORAGE

Precautions for Safe Handling: Avoid contact with the eyes. Avoid prolonged contact with skin and clothing. Avoid breathing vapors and mists. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use.

Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a dry, well-ventilated area. Protect from physical damage. Keep container closed when not in use.

SECTION 8 EXPOSURE CONTROLS and PERSONAL PROTECTION

Exposure Guidelines:

INGREDIENTS	EXPOSURE LIMITS
Carbon Black	3.5 mg/m³ TWA OSHA PEL
	3 mg/m3 TWA ACGIH TLV (inhalable)

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits.

Primeseal 1 Page 2 of 5



Respiratory Protection: If the exposure limits are exceeded a NIOSH approved respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Gloves: Nitrile rubber or other impervious gloves are recommended to prevent prolonged skin contact.

Eye Protection: Chemical safety goggles should be worn if splashing is possible.

Other Protective Equipment: Impervious clothing as needed to avoid prolonged skin contact. For operations where contact can occur, a safety shower and an eye wash facility should be available.

SECTION 9 PHYSICAL and CHEMICAL PROPERTIES

Appearance And Odor: Black liquid with a mild odor.

Boiling Point (@ 760 mmHg): >212°F (>100°C)	Freezing Point: Not available
Odor Threshold: Not determined	Viscosity: Not determined
Relative density (H2O=1): Not available	Vapor Pressure: Same as water
VOC: Not available	Vapor Density (AIR=1): >1
Evaporation Rate: Same as water	Solubility In Water: Miscible
pH: not available	Partition Coefficient n-Octanol/Water: Not available
Flash Point: Not flammable	Autoignition Temperature: Not applicable
Decomposition Temperature: Not determined	Flammability (solid, gas): Not applicable
Flammable Limits: (vol % in air) LEL – Not applicable UEL – Not applicable	

SECTION 10 STABILITY and REACTIVITY

Reactivity: Not normally reactive.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known.

Conditions to avoid: None known. Incompatible materials: None known.

Hazardous decomposition products: Thermal decomposition may yield oxides of carbon.

SECTION 11 TOXICOLOGICAL INFORMATION

Eye: Contact may cause mild irritation with redness and tearing.

Skin: Prolonged skin contact may cause mild irritation and drying of the skin.

Inhalation: Inhalation of vapors or mists may cause mucous membrane and upper respiratory tract irritation.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sensitization: This product is not expected to cause sensitization.

Chronic Effects: None known.

Carcinogenicity: Carbon black is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B. None of the other components present at 0.1% or greater are listed as a carcinogen by NTP, IARC, ACGIH or OSHA. The carbon black is inextricably bound so no exposure is expected.

Numerical Measures of Toxicity:

Carbon black: Oral rat LD50: >8000 mg/kg

Primeseal 1 Page 3 of 5



SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Carbon Black: 96 hr LD0 Danio rerio 1000 mg/L, 24 hr EC50 daphnia magna >5600 mg/L, 72 hr EC50 Desmodesmus subspicatus

>10000 mg/L

Persistence and degradability: No data available Bioaccumulative potential: No data available

Mobility in soil: No data available Other adverse effects: No data available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with all local, state and federal regulations.

SECTION 14: TRANSPORT INFORMATION

DOT:

UN/ID Number None

Proper Shipping Name Not Regulated

Hazard Class None Packing Group None **ERG Code** N/A

DOT Special Provisions None known

Description None

TDG:

UN/ID Number None

Proper Shipping Name Not Regulated

Hazard Class None Packing Group None ERG Code N/A

TDG Special Provisions None known

Description None

IATA:

UN/ID Number None

Proper Shipping Name Not Regulated

Hazard Class None Packing Group None ERG Code N/A

Special Provisions None known

Description None

IMDG:

UN/ID Number None

Proper Shipping Name Not Regulated

Hazard Class None Packing Group None EmS-No N/A

Special Provisions None known

Description None

Primeseal 1 Page 4 of 5



Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None known

SECTION 15: REGULATORY INFORMATION

SARA Hazard Category (311/312): Refer to Section 2 for OSHA Hazard Classification

EPA SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313: None

CERCLA Hazardous Substances (Section 103)/RQ: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory.

California Proposition 65: This product contains chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: OTHER INFORMATION

NFPA Rating:Health = 1Fire = 0Instability = 0HMIS Rating:Health = 1^* Fire = 0Physical Hazard = 0

SDS Date of Preparation: 11/3/17

Revision Summary: Header, Section 14 Transportation, Section 15 SARA 311/312

NOTICE

The information contained herein is based upon the data available to us and is believed to be accurate. However, KM Coatings Mfg. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. KM Coatings Mfg. assumes no responsibility for injury from the use of the products described herein.

This SDS conforms with the OSHA Hazard Communication Standard 1900.1210 and to SARA Title III, Section 313 for supplier notification.

Primeseal 1 Page 5 of 5