

Tietex T272

Stitchbonded Polyester Mesh

Description

Tietex T272 is a white, 3 ounce stitchbonded polyester fabric used in the reinforcement of cold process roofing systems and also as a reinforcement with mastics and elastomerics.

Uses

The flexible nature of this fabric allows for ease of application over the critical corrugations and laps found in metal roofing and conforms with smooth and semi-smooth surfaces. This product may require light brooming or dry rolling to insure good embedment and removal of any air pockets

Packaging

- 4" × 300' Roll
- 6" × 300' Roll
- 12" × 300' Roll
- 20" × 300' Roll
- 40" × 324' Roll

Typical Physical Properties

1. **Tensile Strength (lb)** MD: 67; CD: 59, ASTM D5034
2. **Trapezoid Tear (lb)** MD: 22; CD: 21, ASTM D5587
3. **Elongation (lb)** MD: 25; CD: 79, ASTM D5034
4. **Thickness (in)** .018, ASTM D1777
5. **Ball Burst (lb)** 109, ASTM D3787

Refer to Safety Data Sheet (SDS) for specific data and handling of our products.



KM Coatings

1719 West Buchanan Street
Phoenix, Arizona 85007

Office: (602) 253-1168
Fax: (602) 258-1887
Toll Free: (800) 982-6899

Refer to SDS for specific data and handling of our products.

All data furnished refers to standard production using manufacturing testing tolerances. The product user, and not KM Coatings, is responsible for determining the suitability and compatibility of our products for the user's intended use.