

Safety Data Sheet

KM PS# 250.2 - HIGH SOLIDS SILICONE ROOF COATING

Safety Data Sheet dated: 01/14/2022 - version 3

Date of first edition: 08/13/2021



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: KM PS# 250.2 - HIGH SOLIDS SILICONE ROOF COATING

Trade code: PLY0082

Recommended use of the chemical and restrictions on use

Recommended use: Coating

Restrictions on use: N.A.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: KM Coatings Mfg.

5301 W. Mohave Street

85043 - Phoenix - AZ - USA

Phone: 602-253-1168

Responsible: Not available

Emergency 24 hour numbers:

Chemtrec (800) 424-9300

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flam. Liq. 4	Combustible liquid
Skin Irrit. 2	Causes skin irritation.
Eye Dam. 1	Causes serious eye damage.
Skin Sens. 1B	May cause an allergic skin reaction.
STOT RE 2	May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.
Acute Tox. 4	Harmful if swallowed.
Repr. 2	Suspected of damaging fertility or the unborn child.

Label elements

Pictograms and Signal Words



Danger

Hazard statements:

H227	Combustible liquid
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Precautionary statements:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P260	Do not breathe mist/vapours/spray.

P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312	IF SWALLOWED: Call a POISON CENTER if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER.
P330	Rinse mouth.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
10-20 %	Silica Sand	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350	
5-10 %	TITANIUM DIOXIDE	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	Carc. 2, H351	
2.5-5 %	2-BUTANONE, O,O',O''-(METHYLSILYLIDYNE)TRIOXIME	CAS:22984-54-9 EC:245-366-4	Eye Irrit. 2A, H319; Skin Sens. 1B, H317; STOT RE 2, H373	
2.5-5 %	3-(TRIETHOXSILYL)PROPYLAMINE	CAS:919-30-2 EC:213-048-4 Index:612-108-00-0	Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1B, H317; Skin Corr. 1B, H314	
0.25-0.49 %	OCTAMETHYLCYCLOTETRASILOXANE	CAS:556-67-2 EC:209-136-7 Index:014-018-00-1	Flam. Liq. 3, H226; Repr. 2, H361; Aquatic Chronic 4, H413	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Give nothing to eat or drink.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
Silica Sand	ACGIH			0.025					A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;
	ACGIH			0.025					A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA		0.15					
TITANIUM DIOXIDE	MAK	SWITZERLAND		0.15					
	OSHA			15					
	ACGIH			10					A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation;
	MAK	GERMANY		0.3					
	ACGIH			10					A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation
	MAK	AUSTRIA		5		10			
	MAK	SWITZERLAND		3					

Appropriate engineering controls: N.A.

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: viscous liquid

Odour: almost odorless

Odour threshold: Not Relevant
pH: Not Relevant
Melting point / freezing point: Not Relevant
Initial boiling point and boiling range: Not Relevant
Flash point: 88 °C (190 °F)
Evaporation rate: Not Relevant
Upper/lower flammability or explosive limits: Not Relevant
Vapour density: Not Relevant
Vapour pressure: Not Relevant
Relative density: 1.32 g/cm³
Solubility in water: Insoluble
Solubility in oil: Not Relevant
Partition coefficient (n-octanol/water): Not Relevant
Auto-ignition temperature: Not Relevant
Decomposition temperature: Not Relevant
Viscosity: Not Relevant
Explosive properties: Not Relevant
Oxidizing properties: Not Relevant
Solid/gas flammability: Not Relevant

Other information

Substance Groups relevant properties Not Relevant
Miscibility: Not Relevant
Fat Solubility: Not Relevant
Conductivity: Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information on main components of the mixture:

Silica Sand	a) acute toxicity	LD50 Oral Rat = 500 mg/kg
TITANIUM DIOXIDE	a) acute toxicity	LD50 Oral Rat > 10000 mg/kg
3-(TRIETHOXSILYL) PROPYLAMINE	a) acute toxicity	LD50 Skin Rabbit = 4290 mg/kg LC50 Inhalation Rat > 735 mg/l 4h LD50 Oral Rat = 1780 mg/kg LC50 Inhalation Rat > 7.35 mg/l 4h
OCTAMETHYLCYCLOTETR ASILOXANE	a) acute toxicity	LD50 Skin Rabbit = 794 µL/kg LC50 Inhalation Rat = 36 g/m ³ 4h LD50 Oral Rat = 1540 mg/kg LD50 Skin Rabbit = 794 µL/kg

Substance(s) listed on the IARC Monographs:

Silica Sand Group 1
TITANIUM DIOXIDE Group 2B

Substance(s) listed as OSHA Carcinogen(s):

Silica Sand
TITANIUM DIOXIDE

Substance(s) listed as NIOSH Carcinogen(s):

Silica Sand
TITANIUM DIOXIDE

Substance(s) listed on the NTP report on Carcinogens:

Silica Sand

12. ECOLOGICAL INFORMATION**Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
Silica Sand	CAS: 14808-60-7 - EINECS: 238-878-4	a) Aquatic acute toxicity : LC50 carp > 10000.00000 mg/L 72h
3-(TRIETHOXSILYL)PROPYLAMINE	CAS: 919-30-2 - EINECS: 213-048-4 - INDEX: 612-108-00-0	a) Aquatic acute toxicity : LC50 Fish Danio rerio > 934 mg/L 96h ECHA
OCTAMETHYLCYCLOTETRASIOXANE	CAS: 556-67-2 - EINECS: 209-136-7 - INDEX: 014-018-00-1	a) Aquatic acute toxicity : LC50 Fish Brachydanio rerio > 500 mg/L 96h IUCLID
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus > 1000 mg/L 96h IUCLID

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS**Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information,

contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

ADR-UN number: NA1993

DOT-UN Number: NA1993

IATA-Un number: -

IMDG-Un number: -

UN proper shipping name

ADR-Shipping Name: - (OCTAMETHYLCYCLOTETRASILOXANE)

DOT-Proper Shipping Name: Combustible liquid, n.o.s. (OCTAMETHYLCYCLOTETRASILOXANE)

IATA-Technical name: - (OCTAMETHYLCYCLOTETRASILOXANE)

IMDG-Technical name: - (OCTAMETHYLCYCLOTETRASILOXANE)

Transport hazard class(es)

ADR-Class: -

DOT-Hazard Class: Comb liq

IATA-Class: -

IMDG-Class: -

Packing group

ADR-Packing Group: -

DOT-Packing group: III

IATA-Packing group: -

IMDG-Packing group: -

Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 148, IB3, T1, TP1

DOT-Label(s): -

DOT-Symbol: N/A

DOT-Cargo Aircraft: N/A

DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A

DOT-Non-Bulk: N/A

Road and Rail (ADR-RID) :

ADR-Label: -

ADR-Hazard identification number: -

ADR-Transport category (Tunnel restriction code): -

Air (IATA) :

IATA-Passenger Aircraft: -

IATA-Cargo Aircraft: -

IATA-Label: -

IATA-Subsidiary hazards: -

IATA-Erg: -

IATA-Special Provisioning: -

Sea (IMDG) :

IMDG-Stowage Code: -

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: -

IMDG-Page: N/A

IMDG-Label: N/A

IMDG-EMS: -

IMDG-MFAG: N/A

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

Silica Sand is listed in TSCA Section 8b

TITANIUM DIOXIDE is listed in TSCA Section 8b

2-BUTANONE, O,O',O''-(METHYLSILYLIDYNE)TRIOXIME is listed in TSCA Section 8b

3-(TRIETHOXSILYL)PROPYLAMINE is listed in TSCA Section 8b

OCTAMETHYLCYCLOTETRASILOXANE is listed in TSCA Section 8b Section 8a - PAIR Section 12b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Silica Sand Listed as carcinogen

TITANIUM DIOXIDE Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Silica Sand

TITANIUM DIOXIDE

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Silica Sand

TITANIUM DIOXIDE

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Silica Sand

TITANIUM DIOXIDE

Canada - Federal regulations**DSL - Domestic Substances List****DSL Inventory:**

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List**NDSL Inventory:**

No substances listed

NPRI - National Pollutant Release Inventory**Substances listed in NPRI:**

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 1/14/2022 - version 3

Additional classification information

NFPA Health: 2 = Moderate

NFPA Flammability: 2 = Combustible liquid

NFPA Reactivity: 0 = Minimal

NFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H226	Flammable liquid and vapour.
H227	Combustible liquid
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.
H413	May cause long lasting harmful effects to aquatic life.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 4. FIRST AID MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION